

agroliner Two-axle three-way tipper

Type: HKD 302 18 tonne permissible total weight

Standard equipment:

| | |
|-------------------------------|--|
| <i>Tyres:</i> | 4x 385/65 R22.5 factory refurbished tyres on centre well rims 80 km/h |
| <i>Axles:</i> | ADR tapered roller bearing axles, 11.3 tonnes axle load (105 km/h), 2050 mm track width, without ABS up to 60 km/h, wheel brake 406 x 120 mm, 130 mm square axle |
| <i>Springs:</i> | 18 tonne 2 layer parabolic spring suspension, 100 mm wide, approved for up to 105 km/h Overload protection for the rear parabolic spring suspension |
| <i>Steering:</i> | Turntable steering with ball bearing turntable and type-tested triangular drawbar 1,990 mm long, Height adjustable as well as drawbar relief |
| <i>Chassis frame:</i> | welded steel construction; double T main load bearer |
| <i>Brake system:</i> | dual line service brake system with automatic load-dependent brake force control (ALB), 4 x diaphragm brake cylinder, spindle parking brake for the rear axle |
| <i>Tipping system:</i> | 3-way tipper; hydraulic multi-piston press with cardanic suspension, 1 line system, ball tipper bearings with retainer at the rear, 2 unmistakable locking pins, hydraulic stroke limiter, safety rope |
| <i>Tipper frame:</i> | profile steel in welded construction, 4 mm steel floor plate |
| <i>Bulkhead:</i> | fixed made from webbed combined multiplex board 18 mm, WBP pasted, green plastic-coat PPL one-sided at the outside, in the area of the side board walls, use of stainless steel VA bolts, fixed corner rungs, steps on the drawbar, ergonomic access ladder with catwalk and accident protection bar according to the German accident prevention regulations (UVV), folded step outside and on the inside of the bulkhead |
| <i>Side board walls:</i> | webbed combined multiplex board as with the bulkhead embedded in aluminium profile (with integrated water drain) with robust rubber seals that can be replaced, 2 side board walls each without horizontal partitioning, fixed centre posts with 2 removable connecting tubes, split, central bottom unlocking, bottom unlocking lever at the front and rear with top dead point tensioner, optimally designed for the equipping of an automatic side board wall remote unlocking system |
| <i>Tailgate:</i> | basic design is the same as the side board wall with an 1 grain feed in the middle (480 x 290 mm) with lever operation (left side) and removable discharge chute, fixed corner stanchions, central bottom unlocking, bottom unlocking lever on the left side with top dead point tensioner |
| <i>Electrical system:</i> | 12 Volt system according to the guidelines of the StVZO (German traffic laws) with 7-pin connecting cable, triangular reflector and yellow side reflectors, 3 function rear lights (rubber mounted), number plate lights, position lights |
| <i>Accessories:</i> | stable underride protection, number plate bracket, wheel chocks with bracket, plastic mudguard at the rear, park sockets for all connections on the drawbar, protective caps on the screw connections, resting point supports for tipping bridge for reducing the noise during driving operation |
| <i>Paintwork:</i> | vehicle blasted with steel grit and also degreased, chip-resistant primer, sealing of areas in particular risk of corrosion using bodywork sealing compound, top coat in German quality dual-component gloss paint Assembly: Kröger green, panels = outside covered with "green" plastic-coat PPL, UV resistant Chassis: Kröger red |
| <i>Technical data:</i> | permissible total weight: 18,000 kg Empty weight: approx. 4,100 kg (in the basic equipment) Payload: approx. 13,900 kg Catwalk height: approx. 1,330 mm (in the basic equipment) Oil requirement: approx. 19.9 litres |
| <i>Cargo area dimensions:</i> | outside: approx. L 5,300 mm x W 2,550 mm x H 1,300 mm inside: approx. L 5,235 mm x W 2,420 mm x H 1,300 mm Panel width also between the middle and corner stanchions! |


Basic price *agroliner* Type: HKD302



Ancillary equipment subject to charge:


A SUPERSTRUCTURE

- A 0500 LIGHT version, weight-optimised version Weight saving of up to 150 kg (depending on the equipment) Floor plate 3 mm instead of 4 mm. No loss in stability by using high-tensile special steels
- A 0600 Side panels with plastic lightweight panels, 20 mm thick, side board wall height 1500 mm, (colour white or in combination with L 1200, not suitable for direct filling by woodchippers),
- A 2100 Side board wall height 1500 mm instead of 1300 mm
- A 2610 "Shock-Stop" potato chute (conveyor belt rubber) in the front cargo area
- A 2650 5 x lashing eyes recessed in the body floor on both sides
- A 2700 Mobile aluminium stepladder clamped onto the bulkhead
- A 2800 Viewing window with guard grille in the bulkhead
- A 2910 Continuous bottom unlocking shafts on the right + left side with 2 x top dead point tensioner at the bulkhead
- A 2930 Operation of the bottom unlocking system for the rear side board walls on the right and left sides via separate top dead point tensioners at the bulkhead (then a total of 4 items)
- A 3000 Side tipping bridge extension 200 mm high, can be mounted on both sides
- A 3100 Side tipping bridge extension 200 mm high, mounted on both sides
- A 3150 Side bottom unlocking hooks, with threaded bushings on both sides
- A 3200 Removable rear tipping bridge extension, over the whole vehicle width (W 2480 mm x L 350 mm)
- A 4000 Hydraulic side board wall remote unlocking system, can be mounted on both sides, with connection for a 2nd vehicle
- A 4100 Hydraulic side board wall remote unlocking system, can be mounted on both sides, with connection for a 2nd vehicle
- A 4150 Brackets for the hydraulic side board wall remote unlocking system on both sides, without hydraulic lines and stamp
- A 4310 "SMART LOCK" hydraulic side board wall central locking on one side for automatic opening and closing of the side board walls (including closures at half height) with connection for a 2nd vehicle (double-acting control unit required, not in conjunction with A 3000, A 8000, A 9050, A 9300 or A 9500)
- A 5700 Additional slide gate with chute in the tailgate (total of 2 items right + left)
- A 5710 2 x additional slide gates with chute in the tailgate (total of 3 items)
- A 6000 Plug-in triangle at the front and rear (300 mm) + middle triangle with foldable roof arch
- A 7000 Yellow tarpaulin with aluminium roller board, hand crank and removable stop supports on the side
- A 7100 Yellow tarpaulin (reinforced material) with aluminium roller board, hand crank and removable stop supports on the side (can be fastened on the side with 2 x strap ratchets)
- A 7200 Yellow tarpaulin, can be operated from both sides with aluminium roller pipes, hand crank and stop supports on both sides that can be re-positioned (can be fastened on the side with 4 x expander cables)
- A 7300 Yellow tarpaulin (reinforced material), can be operated from both sides with aluminium roller pipes, hand crank and stop supports on both sides that can be re-positioned (can be fastened on the side with 4 x strap ratchets)
- A 8000 Side board walls partitioned horizontally with rubber sealing system, on one side left or right only
- A 8100 Side board walls partitioned horizontally with rubber sealing system, partitioned on both sides left or right
- A 8200 Tailgate partitioned horizontally with rubber sealing system
- A 8400 Centre post partitioned (per side)
- A 8450 Centre post partitioned on both sides, right and left
- A 9050 Centre post can be folded and removed completely, on one side left or right only
- A 9200 Tailgate as portal can be pivoted open by 270°
- A 9300 Side board walls also as portal can be pivoted open to the outside from the middle, including adjustable eccentric bolts, per side
- A 9500 Continuous, reinforced swivel side panel on one side without a centre post



F CHASSIS

- F 1000 Automatic trailer coupling including light, pneumatic and hydraulic connections for a 2nd trailer
- F 1600 Underride protection made from round pipe with lighting equipment relocated upwards
- F 1800 Plastic mudguards for the front axle
- F 2850 Drawbar support for drawbar type Klemmfix



- F 2900 Plastic toolbox, dimensions: W 600 x D 500 x H 400
- F 3000 Length-adjustable Y-drawbar (adjustment range 1,500-2,100 mm)
- F 3050 Reinforced Y-drawbar (26 tonnes), 1900 mm long
- F 3080 Drawbar 18 tonnes 2100 mm long instead of 1900 mm (necessary behind a tandem trailer)
- F 4000 A.B.S. 24 Volt
- F 4640 Additional ALB valve mounted on the rear axle
- F 4650 Separate release valve for front axle
- F 4680 Brake system with Duomatik couplings
- F 5100 Side marking lights (LED)
- F 5140 Contour marking film, yellow on the side and rear of the vehicle (mandatory for approval > 60 km/h)
- F 5160 Position and number plate lights as LED version
- F 5180 3 function rear lights, angular, LED version, incl. indicator failure check
- F 5200 5 function rear lights with fog light and reversing light (7-pin 24 Volt connection required)
- F 5260 Protective grids for the rear lights, screw-on version
- F 5290 Hydraulic hose marking "Kennfixx" (price per hydraulic pipe)
- F 5300 Actuation of the 2nd trailer tipping mechanism with separate hydraulic connection and gate valve
- F 5310 3/2-directional valve for the tipping hydraulics (instead of standard gate valve)
- F 5330 Additional gate valve for the 2nd trailer hydraulic connection on the drawbar
- F 5400 Separate oil stub line to the rear (diameter 15 mm)
- F 5420 Assembly of a front screw conveyor (without screw only in combination with F 5400)
- F 6320 12 tonnes ADR axles (105 km/h), reinforced, 2050 mm track, without ABS and automatic slack adjuster, wheel brake 420 x 180 mm, 150 mm square axle
- F 6450 9 tonnes GIGANT axles (105 km/h), 2040 mm track, without ABS and automatic slack adjuster, wheel brake 420 x 180 mm (approved only for tyres 445/65R22.5)
- F 6550 9 tonnes GIGANT axles (105 km/h), 2040 mm track, ABS fitted, automatic slack adjuster, wheel brake 420 x 180 mm (approved only for tyres 445/65R22.5)

| |
|--|
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |
| |

R WHEELS

- R 2000 Tyres, "new" 385/65R22.5 (105 km/h) manufacturer PIRELLI Triathlon (EU Tyre Label B,A,70)
- R 2100 Tyres, factory refurbished 425/65R22.5 (80 km/h) (catwalk height approx. + 50 mm)
- R 2200 Tyres, "new" 425/65R22.5 (105 km/h) manufacturer Continental (catwalk height approx. + 50 mm)
- R 2400 Tyres, "new" 445/65R22.5 (105 km/h) manufacturer Continental (catwalk height approx. + 60 mm)
- R 2460 Tyres, "new" 560/60R22.5 BKT FLOTATION RADIAL, profiles FL 693 M, (70 km/h), (tyre load at 1.5 bar 10 km/h = 4,010 kg) (catwalk height approx. + 220 mm), rims with imprint depth ID + 30 mm
- R 2590 Tyres "new" 560/60R22.5 NOKIAN Country King (65 km/h) 161D with reinforced rims 20.00 (tyre load at 1.5 bar 10 km/h = 5,000 kg) (catwalk height approx. + 220 mm)
combined driving!

| |
|--|
| |
| |
| |
| |
| |
| |

L PAINTWORK

- L 1000 Special paintwork, chassis according to RAL tone
- L 1100 Special paintwork, rims according to RAL tone
- L 1200 Special paintwork, superstructure and side board walls according to RAL tone
- L 1500 Stone chipping protection coating under the tipping bridge in the area above the wheels

| |
|--|
| |
| |
| |
| |

T EXPERT'S REPORT/HANDING OVER

- T 1500 Expert's report for 40 km/h registration
- T 2000 Expert's report for 60 km/h registration
- T 3000 Expert's report for 105 km/h registration (only with F4000, F5100, F 5140, F5200, F6550, R 2000)
- T 9000 Transport costs, German post code 0-4
- T 9100 Transport costs, German post code 5-9

| |
|--|
| |
| |
| |
| |
| |

All prices indicated are subject to legal VAT.

Version: October 2019

Peter Kröger GmbH – Nutzfahrzeuge • Bloge 4 • D 49429 Visbek - Rechterfeld
T: 04445/9636-0 F: 9636-66 E: info@kroeger-nutzfahrzeuge.de W: www.kroeger-nutzfahrzeuge.de